TECHNICAL DATA SHEET

THERMATAPE"

SELF-ADHESIVE THERMAL BREAK STRIP

Product description and typical applications


Thermatape™ is a high density polyethylene foam strip featuring a self-adhesive backing for easy adhesion to steel frames and lightweight cladding materials. Its Material R-value deems it compliant to the National Construction Code (NCC) requirement stipulating the incorporation of an R0.2 thermal break in applications where thermal bridging will occur.

ThermatapeTM works by creating a thermal break between the steel frame and the outer cladding material. The high density polyethylene foam prevents direct contact between the steel frame and the cladding at the fixing point, ensuring the overall thermal performance of the system is not adversely affected by thermal bridging.

Physical characteristics

Material R-value m ² K/W	Nominal thickness mm	Width mm	Length per roll m	Product code
0.2	10	30	10	318004

Cross section diagram



Specification notes

The thermal break material shall be Fletcher Insulation Thermatape™ thermal break strips 30mm x 10m x 10mm.

© Fletcher Insulation Pty Limited 2016. Fletcher Insulation reserves the right to change product specifications without prior notification. Information in this publication and otherwise supplied to users as to the subject product is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of products, no warranty is given or is to be implied with respect to either such information or the product itself, in particular the suitability of the product for any particular purpose. The purchaser should independently determine the suitability of the product for the intended application. Unless otherwise stated all TM and ® are trademarks and registered trademarks of Fletcher Insulation Pty Limited ABN 72 001 175 355.

RTDS6_Revision_0_Issue Date 13012016



1300 654 444